Edelbrock CYLINDER HEADS VALVE SPRINGS & RETAINERS

| Valve Springs | Application | Туре | Seat Pressure | Installed Height | Open Pressure | 0.D. | I.D. | Coil Bind | Retainers | Locks | Recommended Edelbrock Cam |
|--|---|----------------------------|----------------------|---------------------|--------------------------------------|------------------|------------------|------------------|----------------|-------------------------|--|
| AMC 290- | -304-360-390-401 V8 '70 | & LATER | | | | | | | | | |
| #5832 | Cast-Iron O.E. Head | Non-Rotator | 89 lbs. | 1.812" | 200 lbs. @ .425" | 1.364" | 1.000" | 1.300" | #9720 | See Lock Chart | #2132 Performer Cam |
| #5932 | Cast-Iron O.E. Head | Rotator | 89 lbs. | 1.625" | 200 lbs. @ .425" | 1.408" | 1.010" | 1.300" | - | - | #2132 Performer Cam |
| #5792 | Edelbrock #60119 / #60139 | Non-Rotator | 132 lbs. | 1.900" | 312 lbs. @ .500" | 1.550" | 1.120" | 1.160" | #9644 | #9616 | #2132 Performer/ #7132 RPM Cams |
| | 0-430-455 V8 | N. D. | 100 !! | 1.000 | 010 @ 500 | 1 550 | 1 100 | 1 100 | 110044 | 11004.0 | A1/A |
| #5792 | Edelbrock #60049 ET 200-229-262 90° V6 | Non-Rotator | 132 lbs. | 1.900" | 312 lbs. @ .500" | 1.550 | 1.120" | 1.160 | #9644 | #9616 | N/A |
| CHEVRUL | E1 200-229-202 90 VO | | | | | | | | | | #2112 / #3790 |
| #5813 | Cast-Iron O.E. Head | Non-Rotator | 80 lbs. | 1.700" | 200 lbs. @ .475" | 1.222" | | 1.150" | #9720 | See Lock Chart | #2112 / #3790 Performer Cams #2112 / #3790 |
| #5913 | Cast-Iron O.E. Head .ET 4.3L 90° V6 '87-95 | Rotator | 80 lbs. | 1.610" | 200 lbs. @ .475" | 1.222" | 0.875" | 1.150" | - | - | Performer Cams |
| #5814 | Cast-Iron O.E. Head | Non-Rotator | 110 lbs. | 1.700" | 285 lbs. @ .490" | 1 250" | 0.750" | 1 160" | #9729 | See Lock Chart | #3714 Performer Cam |
| | ET 262-400 V8 '57-95 | NUII-NUIdiUI | 110105. | 1.700 | 200 108. @ .490 | 1.230 | 0.730 | 1.100 | #3723 | See Lock Chart | |
| #5802 (B) | Cast-Iron O.E. Head | Non-Rotator | 80 lbs. | 1.700" | 200 lbs. @ .475" | 1.222" | 0.875" | 1.150" | #9721 | See Lock Chart | #2102 / #2103 / #3702 Performer Cams |
| #5902 (B) | Cast-Iron O.E. Head | Rotator | 80 lbs. | 1.610" | 200 lbs. @ .475" | 1.222" | 0.875" | 1.150" | - | See Lock Chart | #2102 / #2103 / #3702 Performer Cams |
| # 5894 (E) | Cast-Iron O.E. Head | Non-Rotator | 80 lbs. | 1.700" | 200 lbs. @ .475" | 1.222" | 0.875" | 1.150" | #9721 | See Lock Chart | #2102, #2103, #3702 Performer Cams |
| #5703 | Cast-Iron O.E. Head | Non-Rotator | 110 lbs. | 1.700" | 285 lbs. @ .490" | 1.265" | 0.880" | 1.160" | #9730 | See Lock Chart | #2208 / #2209 / #7102, #5002 Cams |
| #5794 (E) | Cast-Iron O.E. Head E-Street Heads | Non-Rotator Non-Rotator | 110 lbs. 120 lbs. | 1.700" 1.800" | 285 lbs. @ .490" 310 lbs. @ .580" | 1.265" 1.460" | | 1.160" 1.150" | #9730 #9736 | See Lock Chart #9611 | #2208 / #2209 / #7102, #5002 Cams |
| #5767 (F) #5825 (N) | Performer / RPM Heads | Non-Rotator | 120 lbs. | 1.800" | 338 lbs. @ .580" | 1.460" | | 1.150" | #9741 | #9611 | All Performer Cams All Flat Tappet Cams |
| #5845 | Performer, Performer RPM, E-Tec Heads and E-CNC Head #79895 | Non-Rotator | 150 lbs. | 1.800" | 420 lbs. @ .580" | | 1.060" | | #9736 | #9611 | All Hydraulic Roller Cams |
| #5767 (F) | Centerbolt & E-Tec Edelbrock Heads | Non-Rotator | 120 lbs. | 1.800" | 310 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9736 | #9611 | All Performer, RPM & Torker Cams |
| #5821 | E-210 / Victor Jr. Heads | Non-Rotator | 145 lbs. | 1.900" | 345 lbs. @ .600" | 1.540" | 0.760" | 1.130" | #9715 | #9615 | N/A |
| #5823 | Victor Jr. Head | Non-Rotator | 210 lbs. | 1.900" | 510 lbs. @ .600" | 1.540" | 0.731" | 1.170" | #9715 | #9615 | N/A |
| #5767 | Edelbrock LT1 #61909 | Non-Rotator | 120 lbs. | 1.800" | 310 lbs. @ .580" | 1.460" | 1.060" | | #9736 | #9616 | #2108 |
| #5768 | Edelbrock LT4 #61939 | Non-Rotator | 138 lbs. | 1.800" | 326 lbs. @ .600" | (L) | (M) | 1.140" | #9707 | #9657 | #2108 |
| #5768 | . ET LS1 V8 O.E. Head | Non-Rotator | 138 lbs. | 1.800" | 326 lbs. @ .600" | (L) | (M) | 1.140" | #9707 | See Lock Chart | #2215 / #2216 / #2217, |
| #5768 | Edelbrock Heads | Non-Rotator | 138 lbs. | 1.800" | 326 lbs. @ .600" | (L) | (M) | 1.140" | #9707 or | #9657 | #2218 / #2219 Cams #2215 / #2216 / #2217, |
| CHEVROL | ET 348/409 W-SERIES V | /8 | | | | | | | #9708 | | #2218 / #2219 Cams |
| #5792 | Edelbrock #60819 | Non-Rotator | 130 lbs. | 1.900" | 355 lbs. @ .600" | 1.550" | 1.120" | 1.160" | #9715 | #9616 | N/A |
| | ET 396-402-427-454 V8 | | | 4.0 | | | | | | | "0100 P. (|
| #5862 | Cast-Iron O.E. Head | Non-Rotator | 90 lbs. | 1.880" | 220 lbs. @ .420" | | 1.082" | | #9720 | See Lock Chart | #2162 Performer Cams |
| # 5895 (E) # 5762 (C) | Cast-Iron O.E. Head Cast-Iron O.E. Head | Non-Rotator Non-Rotator | 90 lbs. 100 lbs. | 1.880" 1.880" | 220 lbs. @ .420" 300 lbs. @ .580" | | 1.082" 0.800" | | #9720 #9731 | See Lock Chart #9612 | #2162 Performer Cams All Performer, RPM |
| #5795 (C,E) | Cast-Iron O.E. Head | Non-Rotator | 100 lbs. | 1.880" | 300 lbs. @ .580" | | 0.800" | | #9731 | #9612 | & Torker Cams All Performer, RPM & Torker Cams |
| # 5745 (G) | E-Street Heads | Non-Rotator | 135 lbs. | 1.975" | 320 lbs. @ .500" | 1.550" | 0.805" | 1.150" | #9602 | #9616 | All Performer Cams |
| # 5745 (G) | RPM/Victor Jr. Hydraulic | Non-Rotator | 135 lbs. | 1.975" | 320 lbs. @ .500" | | 0.805" | | #9602 | #9616 | All Performer, RPM & Torker Cams |
| CALL | Edelbrock Victor Heads | Non-Rotator | 250 lbs. | 2.000" | 800 lbs. @ .850" | 1.640" | 0.860" | 1.070" | | Edelbrock Tec | h 800-416-8628 |
| CHRYSLE | R 318-340-360 V8 1957- | 89 | | | | | | | | | |
| #5877 | Cast-Iron O.E. Head | Non-Rotator | 90 lbs. | 1.650" | 178 lbs. @ .375" | 1.394" | 1.010" | 1.203" | #9720 | See Lock Chart | #2177 Performer Cam |
| #5977 | Cast-Iron O.E. Head | Rotator | 90 lbs. | 1.480" | 187 lbs. @ .400" | | 1.010" | | - | See Lock Chart | #2177 Performer Cam |
| #5777 | Cast-Iron O.E. Head | Non-Rotator | 96 lbs. | 1.650" | 238 lbs. @ .430" | | 1.080" | | #9732 | See Lock Chart | #7177 RPM Cam |
| #5767 (H) | Edelbrock Heads | Non-Rotator | 120 lbs. | 1.800" | 310 lbs. @ .580" | | 1.060" | | #9736 | #9611 | All Performer & RPM Cams |
| #5845 | Performer / RPM Heads | Non-Rotator | 150 lbs. | 1.800" | 420 lbs. @ .580" | 1.460" | 1.060" | 1.150" | #9736 | #9611 | All Hydraulic Roller Cams |



VALVE SPRINGS & RETAINERS CYLINDER HEADS | Edelbrock



| Valve Springs | Application | Туре | Seat Pressure | Installed Height | Open Pressure | 0.D. | I.D. | Coil Bind | Retainers | Locks | Recommended Edelbrock Cam |
|--|--|-----------------------------|------------------|---------------------|------------------|--------|--------|--------------|------------------|----------------|--|
| CHRYSLE | R 383-400-413-440 V8 '6 | 9-79 | | | | | | | | | |
| #5892 | Cast-Iron O.E. Head | Non-Rotator | 125 lbs. | 1.860" | 200 lbs. @ .430" | 1.380" | 1.010" | 1.350" | #9720 | See Lock Chart | #2192 Performer Cam |
| #5992 | Cast-Iron O.E. Head | Rotator | 90 lbs. | 1.730" | 175 lbs. @ .410" | 1.380" | 1.010" | 1.150" | - | See Lock Chart | #2192 Performer Cam |
| #5792 | Cast-Iron O.E. Head | Non-Rotator | 115 lbs. | 1.900" | 280 lbs. @ .500" | 1.550" | 1.120" | 1.160" | #9734 | See Lock Chart | #7194 & #2206 RPM Cams |
| #5792 | Edelbrock #5093 #60189 / #60929 | Non-Rotator | 140 lbs. | 1.880" | 317 lbs. @ .500" | 1.550" | 1.120" | 1.160" | #9644 | #9616 | #2192 Performer, #7194 & #2206 RPM Cams |
| FORD 289 | 9-302 & 351W V8 | | | | | | | | | | |
| #5822 | 289-302 Cast-Iron O.E. | Non-Rotator | 90 lbs. | 1.700" | 210 lbs. @ .400" | 1.354" | 1.010" | 1.200" | #9724 | See Lock Chart | All Performer Cams |
| #5922 | 289-302 Cast-Iron O.E. | Rotator | 85 lbs. | 1.700" | 225 lbs. @ .400" | 1.360" | 0.976" | 1.115" | - | See Lock Chart | All Performer Cams |
| #5882 | 351W Cast-Iron O.E. | Non-Rotator | 65 lbs. | 1.780" | 200 lbs. @ .440" | 1.384" | 1.020" | 1.255" | #9724 | See Lock Chart | All Performer Cams |
| #5982 | 351W Cast-Iron O.E. | Rotator | 65 lbs. | 1.600" | 200 lbs. @ .440" | 1.384" | 1.020" | 1.255" | - | See Lock Chart | All Performer Cams |
| #5896 (E) | 289-302 Cast-Iron O.E. | Non-Rotator | 90 lbs. | 1.700" | 169 lbs. @ .310" | 1.354" | 1.010" | 1.200" | #9724 | See Lock Chart | All Performer Cams |
| #5722 | 289 / 302 / 351W Cast-Iron O.E. | Non-Rotator | 89 lbs. | 1.770" | 233 lbs. @ .390" | 1.438" | 1.024" | 1.260" | #9733 (A) | See Lock Chart | All Flat Tappet Cams |
| #5796 (E) | 351W Cast-Iron O.E. | Non-Rotator | 89 lbs. | 1.770" | 233 lbs. @ .390" | 1.438" | 1.024" | 1.260" | #9733 (A) | See Lock Chart | All Flat Tappet Cams |
| #5767 (F) | E-Street Heads | Non-Rotator | 120 lbs. | 1.800" | 310 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9736 | #9611 | All Performer Cams |
| #5825 (I) | Edelbrock Heads | Non-Rotator | 128 lbs. | 1.80 0" | 338 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9741 | #9611 | All Performer, RPM & Torker Cams |
| #5845 | Performer RPM Heads | Non-Rotator | 150 lbs. | 1.800" | 420 lbs. @ .580" | 1.460" | 1.060" | 1.150" | #9736 | #9611 | All Hydraulic Roller Cams |
| #5768 | Edelbrock #79259 | Non-Rotator | 145 lbs. | 1.800" | 345 lbs. @ .600" | (L) | (M) | 1.140" | #9707 | #9657 | Rollin Thunder Cams |
| #5821 | E-205 / Victor Jr. Heads | Non-Rotator | 145 lbs. | 1.900" | 380 lbs. @ .600" | 1.540" | . , | 1.130" | #9715 | #9616 | - |
| #5823 | Victor Jr. Head | Non-Rotator | 210 lbs. | 1.900" | 490 lbs. @ .600" | 1.540" | | | #9715 | #9616 | - |
| #5823 Victor Jr. Head Non-Rotator 210 lbs. 1.900" 490 lbs. @ .600" 1.540" 0.731" 1.170" #9715 #9616 - FORD 351M/400 V8 1971-1982 | | | | | | | | | | | |
| #5872 | Cast-Iron O.E. Head | Non-Rotator | 80 lbs. | 1.820" | 226 lbs. @ .430" | 1.400" | 1.000" | 1.330" | #9724 | See Lock Chart | #2172 Performer Cam |
| #5972 | Cast-Iron O.E. Head | Rotator | 80 lbs. | 1.680" | 226 lbs. @ .430" | 1.400" | | 1.330" | π3724 | See Lock Chart | #2172 Performer Cam |
| FORD 351 | | Hotatoi | 00 103. | 1.000 | 220 103. © .400 | 1.700 | 1.000 | 1.000 | | OCC LOCK GHAIT | #ZITZ I CHOINICI Gain |
| #5792 | Edelbrock #61629, #61699 | Non-Rotator | 132 lbs. | 1.900" | 312 lbs. @ .500" | 1.550" | 1.120" | 1.160" | #9644 | #9616 | All Flat Tappet Cleveland |
| FORD 390 |)-428 FE V8 1961-1976 | | | | | | | | | | 0.070.0.10 |
| #5806 | Cast-Iron O.E. Head | Non-Rotator | 90 lbs. | 1.820" | 220 lbs. @ .440" | 1.458" | 1.062" | 1.320" | #9720 | See Lock Chart | #2106 Performer Cam |
| #5906 | Cast-Iron O.E. Head | Rotator | 90 lbs. | 1.680" | 220 lbs. @ .440" | | | 1.320" | π3720 | See Lock Chart | #2106 Performer Cam |
| #5792 | Edelbrock #60069, #60079 | Non-Rotator | 145 lbs. | 1.885" | 355 lbs. @ .580" | | 1.060" | | #9734 | #9612 | All Performer & RPM Cams |
| EORD //20 | 3/460 V8 1969-1987 | | | | | | | | | | C III W Outilo |
| #5867 | Cast-Iron O.E. Head | Non-Rotator | 75 lbs. | 1.820" | 229 lbs. @ .490" | 1.390" | 0.990" | 1.280" | #9724 | See Lock Chart | #2167 Performer Cam |
| #3007 | Cast-IIOII O.E. neau | ויטוו-חטנמנטו | 73 108. | 1.020 | 229 105. @ .490 | 1.330 | 0.550 | 1.200 | #3/24 | See Lock Chart | All Performer |
| #5767 | Cast-Iron O.E. Head | Non-Rotator | 110 lbs. | 1.830" | 290 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9736 | See Lock Chart | & RPM Cams |
| #5745 | Edelbrock #60669, #60679, #61649 | Non-Rotator | 135 lbs. | 1.975" | 320 lbs. @ .500" | 1.550" | | 1.160" | #9715 | #9616 | All Performer & RPM Cams |
| Call | Edelbrock #61669 | N/A | 235 lbs. | 1.950" | 610 lbs. @ 700" | 1.575" | 0.830" | 1.150" | | Edelbrock Tec | 11 000-410-8028 |
| #5812 | 330-350-403 330-350-403 | 984 & 1965-1 Non-Rotator | 80 lbs. | 1.670" | 187 lbs. @ .400" | 1.425" | 1.041" | 1.110" | #9724 | See Lock Chart | #3712 Performer Cam |
| #5712 | Cast-Iron O.E. 330-350-403 Cast-Iron | Non-Rotator | 135 lbs. | 1.750" | | 1.430" | | | #9736 | See Lock Chart | #7112 RPM Cam |
| #5767 | Performer RPM Head #60519 | Non-Rotator | 120 lbs. | 1.800" | 305 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9606 | #9611 | All Performer & RPM Cams |
| #5845 | Performer RPM Head #60515 | Non-Rotator | 150 lbs. | 1.800" | 420 lbs. @ .580" | 1.460" | 1.060" | 1.150" | #9736 | #9611 | All Hydraulic Roller Cams |
| | 389-455 V8 1965-LATER | | | | | | | | | | , |
| #5857 | Cast-Iron O.E. Head | Non-Rotator | 100 lbs. | 1.590" | 242 lbs. @ .470" | 1 390" | 0.768" | N 99N" | #9724 | See Lock Chart | #2157 Performer Cam |
| #5757 | Cast-Iron O.E. Head | Non-Rotator | 112 lbs. | 1.700" | 285 lbs. @ .500" | | 0.830" | | (D) | See Lock Chart | All Performer & RPM Cams |
| #5767 | #60599 / #60579 / #61579 #61599 Heads | Non-Rotator | 120 lbs. | 1.800" | 310 lbs. @ .580" | 1.460" | 1.060" | 1.130" | #9736 | #9611 | All Performer & RPM Cams |
| #5845 | #60575 / #60595 / #61595 #61575 Heads | Non-Rotator | 150 lbs. | 1.800" | 420 lbs. @ .580" | 1.460" | 1.060" | 1.150" | #9736 | #9611 | All Hydraulic Roller Cams |

VALVE SPRING FOOTNOTES

- "O.E." stands for Original Equipment
- (A) Use #9724 to add .100" installed height if needed
- (B) In 305-350 Chevys, some '77 & later vehicles have heads #14014416 (scalloped-out appearance at bottom), use non rotator springs #5802 with stock rotators
- (C) Inner spring will not clear stock valve seal; head must be machined for PC type seals
- (D) Use #99953 from Crane Cams
- (E) Complete spring, retainer & lock kit

- (F) Fits #60859, #60879, #60979, #60989, #5023, #5025, #5089, #5093
- (G) Fits #50459, #79459, #79539, #79559, #60459, #60479, #60499, #60559, #77429, #77479 & #77489
- (H) Fits #60179, #60779 & #61779
- (I) Fits #5028, #60229, #60259, #60329, #60359, #60379 & #60399
- (J) Fits #61409, #77409 & #77459
- (K) Titanium
- (L) O.D. of top 1.066", O.D. of bottom 1.300"
- (M)I.D. of 0.650", I.D. of bottom 0.885"
- (N) Fits #5085, #60759, #60909, #60719, #60739, #60999, #60899 & #79899

PRODUCT EMISSIONS GUIDE