

POWER PKG
KITS
SUPERCHARGERS
CRATE ENGINES
CARBS & ACCESS.
FUEL PUMPS
INSTALL ITEMS
MANIFOLDS
GASKETS
HEADS
EFI
CAMS & ACCESS.
NITROUS
WATER PUMPS
ACCESS.
EXHAUST
SUSPENSION
SHOCKS
QWIKDATA2
INDEX



MANIFOLDS BUICK/CADILLAC AND S/B CHEVY



Edelbrock Intake Manifolds —
An Exclusive NASCAR
Performance Product



Performer Buick/Rover #2198

BUICK/ROVER 215 V8 PERFORMER ROVER (idle-5500 rpm)

Designed for Rover 3500cc V8s (1968 & later) and 1961-63 Buick and Oldsmobile aluminum 215 V8s. Manifold not equipped with EGR. Will not work with OEM carburetors (except Carter AVS).

Performer Rover (non-EGR).....#2198*

Carburetor Recommendations:

Edelbrock Thunder Series AVS or Performer Series carb, 500 cfm (see pages 32-45).

Installation Notes: Recommended intake gasket: **Fel-Pro #MS96002**. Manifold height: A-5.00", B-5.92" (measured to engine block); Carb pad height: 5.46" (see page 54). Port exit dimensions: .88" x 1.54". Throttle Bracket #8031 or #8036 will fit and accepts GM style throttle, kickdown and cruise control cables.



Performer Buick 455 #2146

BUICK 400-455 V8 PERFORMER BUICK 455 (idle-5500 rpm)



Designed for street 400-430-455 c.i.d. Buick V8s. #2146 is stock replacement/street legal part for 400, 430 and 455 V8s; 1967-71; except stock equipped EGR. Manifold not equipped with EGR. Will fit cold air induction hoods. Will not fit Buick 350.

Performer Buick 455 (non-EGR).....#2146

Carburetor Recommendations: OEM 4-bbl.

Edelbrock Thunder Series AVS or Performer Series carb, 650-800 cfm (see pages 32-45).

Installation Notes: Recommended intake gaskets: for 1967-76, **Edelbrock #7246 or Fel-Pro #MS96005**; 1972-76, Fel-Pro #MS96014. #2146 accepts divorced choke-type Quadrajets only. Manifold height: A-3.80", B-4.75"; Carb pad height: 4.27" (see page 54). Port exit dimensions: 1.14" x 2.26".



Buick B-4B #2515

BUICK B-4B (idle-5500 rpm)

Back by popular demand, #2515 is a resurrection of the popular B-4B manifold made in the late 1960s for street 400-430-455 c.i.d. Buick V8s. The only change to the original design is the addition of our proven Performer-style carb pad that accepts either square-bore or spread-bore carbs, making this manifold an excellent choice for both restoration and performance-minded Buick fans.

Buick B-4B (non-EGR).....#2515*

Carburetor Recommendations: OEM 4-bbl.

Edelbrock Thunder Series AVS or Performer Series carb, 650-800 cfm (see pages 32-45).

Installation Notes: Recommended intake gaskets: for 1967-76, **Edelbrock #7246 or Fel-Pro #MS96005**; 1972-76, Fel-Pro #MS96014. Manifold height: A-3.80", B-4.75"; Carb pad height: 4.27" (see page 54). Port exit dimensions: 1.14" x 2.26".



Performer Cadillac #2115

CADILLAC 472-500 V8 PERFORMER CADILLAC (idle-5500 rpm)

This Performer is designed for 1968-76 Cadillac 472 and 500 cubic-inch engines. For either square- or spread-bore carbs, #2115 is the first intake designed specifically for high-performance Cadillacs using standard heads. Like all Edelbrock Performers, this manifold increases torque and horsepower from idle to 5500 rpm. The broad power band is ideal for high-performance street and engine swap applications. Specs on this non-EGR manifold include a carb pad height that's 3" taller than stock. Dropped divider wall evens air/fuel ratio throughout the rpm range. **Stock air conditioning compressor will not fit.**

Performer Cadillac (non-EGR).....#2115*

Carburetor Recommendations: OEM 4-bbl. Edelbrock Thunder Series AVS or Performer Series carb, 750-800 cfm (see pages 32-45).

Installation Notes: When using Quadrajets, #2115 accepts divorced or electric choke only. Recommended intake gasket: **Fel-Pro #MS96028**. Manifold height: A-4.88", B-5.81"; Carb pad height: 5.34" (see page 54). Port exit dimensions: 1.25" x 2.00".



Performer 2V 60° V6 EGR #3785/#3787

CHEVROLET 2.8L V6 PERFORMER 2V 60° V6 (idle-5500 rpm)



Designed for 1982-85 2.8L 60° V6 Chevy longitudinal-mount engines. #3785/#3787 are stock replacement street legal parts for these engines with OEM 2-bbl. carb; 1982-85. For light duty GM pick-ups & passenger cars and 1982-86 Jeep Cherokees with 2.8L. Features base and interchangeable tops. #3787 accepts stock 2-bbl. carb. Edelbrock Signature Series chrome valve covers #4488 are available for this engine, see page 182.

Performer 2V 60° V6 Base.....#3785

Performer 2V 60° V6 Top (EGR).....#3787

Top Gasket (included with top).....#6941

Carburetor Recommendations: OEM 2-bbl. **Installation Notes:** Recommended intake gasket: **Fel-Pro #MS91022**.

Manifold height: A-4.37", B-5.45"; Carb pad height: 4.91" (see page 54). Port exit dimensions: 1.00" x 1.28"/1.00" x 1.71". Linkage and bracketry come with top. Note: When used on Jeep Cherokee, additional hood shimming is required for clearance. Hood shims available from Jeep dealers (part #J0680435).



Performer 4V 60° V6 #3785/#3789

*Not legal for sale or use on pollution controlled motor vehicles.